Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200_Standard must be	U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OME No. 1988-2007			ANN SMITH IN CITY DEPLOCATION		
consulted for specific requirements. IDENTITY RESIN FIBER DISC	A 475 mm	OMB No. 1218-0072 Forms Published by ChemSW TM , Inc. (707)884-0848 Note: Blank spaces are not permitted. If any item is not applicable, or no				
TYPE "C"	information is available, the space must be marked to indicate that.					
Section I						
Manufacturer's Name		Emergency Telephone Number				
GLIT/GEMTEX COMPANY LIMITED	416 245 5605 Telephone Number for Information					
Address (Number, Street, City, State, and ZIP Code) 50 BELFIELD ROAD	· •	416 245 5605				
50 BELIFTED ROAD	Date Prepared	The state of the s				
TORONTO, ONTARIO		3-Jan-01				
	Signature of Prep	Signature of Preparer (optional)				
M9W 1G1, CANADA	n	···		40.43-0		
Section II - Hazardous Ingredients/Identity Informatio	***		Other Limits			
Hezardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Recommended	% (optional)		
VULCANIZED FIBER	N/A	N/A	N/A	45-70		
ALUMINUM OXIDE Al2o3	15 mg/m3	10 mg/m3	1344-28-1	1050		
BINDER SYSTEM	N/A	N/A	N/A	5.0-30		
Section III - Physical/Chemical Characteristics						
Boiling Point	Specific Gravity (Fi2O = 1)		N/A		
N/A	Melting Point			14/22		
Vapor Pressure (mm Hg) N/A				N/A		
Vapor Density (AIR = 1)	Evaporation rate	4)		N/A		
N/A	(Butyl Acetate = 1	1)				
Solubility in Water N/A Appearance and Odor Green backing-odorless						
Section IV - Fire and Explosion Hazard Data			(i =)	UEL		
Flash Point (Method Used)	Flammable Limit	5	N/A	N/A		
N/A Extinguishing Media Water spray, Co2, Foam, Dry chemical or any Special Firefighting Procedures			gent			
Special Hrisighting Procedures Backing & resin binder will burn or decompo	ose. Use resp	orratory prot	eccion.			
N/A						

Section V -	Reactivity D	ata	- I	,	
Stability	Unstable Conditions to Avoid				
				A CONTRACTOR OF THE PARTY OF TH	1,
	Stable	$ \mathbf{x} $	No applicable infor	mation found	
Incompatibility (Materials to Avoid	1)	who resident in the second sec		
Hazardous Dec	omposition or Byp	roduci	is		
		i fu		enerally more fr	om material being ground.
Hazardous Polymerization	May Occur		Conditions to Avoid		
	Will Not Occur	x	No applicable inform	mation found	4
Section VI -	Health Haza				
Route(s) of Entr			inhalation?	Skin?	Ingestion?
Health Hazards	Acute and Chron	ic)	fume/dust during us		Not known nor recommende
Nuisance c	lust, respi	rabl	le - 5mg/m3, total -	15mg/m3, may ir	ritate eyes, elevated sound
level duri	ng use on	some	e metal / jobs.		
	3000000		10		
Carcinogenicity:			NTP?	ARC Monographs?	OSHA Regulated? N/A
			N/A	N/A	47.43
Signs and Symp	oms of Evposure				
Could caus	e coughing	and	i shortness of breatl	n due to dust, ma	y affect breathing, may cause
abrasion o	n skin, du	st m	may irritate eyes.		
Medical Condition	15				
Generally Aggrav	ated by Exposure	;	N/A		Market where the control of
Emergency and	irst Aid Procedu	re		MATTE.	
Remove to	fresh air	if n	leeded, wash eyes wit	h water, obtain	first aid or medical assistant
as deemed	necessary.				
Section VII -	Precautions	for S	Safe Handling and Use		
Steps to be Take N/A	n in Case Materia	l is Re	leased or Spilled		
***			yang yang yang yang yang yang yang yang 		
				- A Parti	
Waste Disposal N	Aethod			****	. het / here het years
No special	procedure	req	wired, standard land	fill consistance	with applicable federal, state
and local	laws.				
- A'	Tales "A Classifie	bna gr	Storage	and OSHA 29C FF	1910.1000 (air contaminates)
					0 - 70 deg. F with ventilation.
Use CAMI (Coated Abr	asiv	e Mfg. Institute) gu	idelines, follow	tool guidelines.
Section VIII -	Control Mea	sure	ès .		. HAR
Respiratory Prote	ction (Specify Typ	oe) e ට්ර	st respirator OSHA 2	4C FR 1910.134	
Ventilation	Local Exhaust			(Special	nformation found
	Recommende Mechanical (Gen			Other	
	Recommende			No applicable i	formation found
Protective Gloves Recommende	3				- Leaves
Other Protective	lothing or Equip	ment	mmended to cover exp	osed skin	
					010 122 0007 20000 1010 124
Eve/face/h	earing pro	tect	ion - (ANSI std. Z87	.I) OSHA ZYÇEK I	910.133 , OSHA 29CFR 1910.134